

An Introduction to Algorithmic Refinement

J.N. Oliveira

Formal Methods II, 2002-06

June 17, 2007

Implicit/explicit refinement

Given VDM-SL implicit specification

```
S(a:A) r:B
pre ...
post ...
```

function $B \xleftarrow{f} A$ is said to **satisfy**, to **refine**, or to **implement** S , written

$$S \vdash f$$

iff, for every a ,

$$\forall a \in A. \text{pre-}S a \Rightarrow \text{post-}S(f a, a)$$

In pointfree notation

$$\begin{aligned} & a \in \delta S \Rightarrow (f a)Sa \\ \equiv & \quad \{ \text{rule } (f b)Ra \equiv b(f^\circ \cdot R)a \} \\ & \delta S \subseteq f^\circ \cdot S \\ \equiv & \quad \{ \text{shunting} \} \\ & f \cdot \delta S \subseteq S \end{aligned}$$

Summary: **explicit** specification (= **implementation**) f is thus more defined and more deterministic than **implicit** specification S :

$$S \vdash f \equiv f \cdot \delta S \subseteq S \quad (1)$$

Example

Recall

```
IsPermutation: seq of int * seq of int -> bool
IsPermutation(l1,l2) ==
  forall e in set (elems l1 union elems l2) &
    card {i | i in set inds l1 & l1(i) = e} =
      card {i | i in set inds l2 & l2(i) = e};
```

We want to find f such that

$$IsPermutation \vdash f$$

Recall that $IsPermutation = \ker seq2bag$, where...

About seq2bag

VDM-SL definition:

```
seq2bag(s) ==
cases s:
  [] -> {}
  others -> { hd s |-> 1 } bunion seq2bag(tl s)
end;
```

Definition of gene g of the seq2bag catamorphism:

$$g = [\{\mapsto\}, \oplus \cdot (singb \times id)]$$

where $singb a = \{a \mapsto 1\}$ and \oplus denotes bag union (bunion is not standard VDM-SL: define it).

Implementing *IsPermutation*

$$\begin{aligned}
 & \text{IsPermutation} \vdash f \\
 \equiv & \quad \{ \text{definition} \} \\
 & f \cdot \delta \text{IsPermutation} \subseteq \text{IsPermutation} \\
 \equiv & \quad \{ \text{definition} \} \\
 & f \cdot \delta (\ker \text{seq2bag}) \subseteq \ker \text{seq2bag} \\
 \equiv & \quad \{ \text{kernel of a function} \} \\
 & f \cdot \text{id} \subseteq \text{seq2bag}^\circ \cdot \text{seq2bag} \\
 \equiv & \quad \{ \text{shunting rule} \} \\
 & \text{seq2bag} \cdot f \subseteq \text{seq2bag} \\
 \equiv & \quad \{ \text{equality of functions} \} \\
 & \text{seq2bag} \cdot f = \text{seq2bag}
 \end{aligned}$$

Handling refinement equations

f is the “unknown” of refinement equation

$$\text{seq2bag} \cdot f = \text{seq2bag}$$

Since seq2bag and f are list catamorphisms, one can resort to cata-fusion,

$$\begin{aligned}
 & \text{seq2bag} \cdot f = \text{seq2bag} \\
 \equiv & \quad \{ \text{let } f = \langle \alpha \rangle \text{ and } \text{seq2bag} = \langle g \rangle \} \\
 & \text{seq2bag} \cdot \langle \alpha \rangle = \langle g \rangle \\
 \Leftarrow & \quad \{ \text{cata-fusion} \} \\
 & \text{seq2bag} \cdot \alpha = g \cdot (\text{id} + \text{id} \times \text{seq2bag})
 \end{aligned}$$

Solving refinement equations

By decomposing $\alpha := [\beta, \gamma]$, we obtain equations

$$\begin{aligned}
 \beta &= \llbracket \quad \rrbracket \\
 \text{seq2bag} \cdot \gamma &= \oplus \cdot (\text{singb} \times \text{seq2bag})
 \end{aligned}$$

- Cata-cancellation yields solution $\gamma = \text{cons}$, leading to $\alpha = \text{in}$ and $f = \text{id}$.
- \oplus is commutative, thus solution $\gamma(a, l) = l \hat{^} [a]$ leading to $f = \text{invl}$.

Guessing further solutions: any list **sorting** function will solve the equation!
(More about this later...)

Properties of \vdash

Basic:

$$\perp \vdash f \quad , \quad \top \vdash f \quad (2)$$

$$(S \cap R) \vdash f \Leftrightarrow S \vdash f \wedge R \vdash f \quad (3)$$

$$(S \cup R) \vdash f \Leftrightarrow S \vdash f \wedge R \vdash f \quad (4)$$

$$(\ker g) \vdash f \equiv g \cdot f = g \quad (5)$$

$$g \vdash f \equiv f = g \quad (6)$$

Monotonicity:

$$S \vdash f \Rightarrow FS \vdash Ff \quad (7)$$

Proof of monotonicity

$$\begin{aligned} & FS \vdash Ff \\ \equiv & \quad \{ \text{definition} \} \\ & (Ff) \cdot \delta(FS) \subseteq FS \\ \equiv & \quad \{ \text{property } \delta(FS) = F(\delta R) \} \\ & (Ff) \cdot F(\delta S) \subseteq FS \\ \equiv & \quad \{ \text{relators commute with composition} \} \\ & F(f \cdot \delta S) \subseteq FS \\ \Leftarrow & \quad \{ \text{relators are monotone} \} \\ & f \cdot \delta S \subseteq S \\ \equiv & \quad \{ \text{definition} \} \\ & S \vdash f \end{aligned}$$

Stepwise refinement

Extend f in $S \vdash f$ to a relation

$$S \vdash R \equiv R \cdot \delta S \subseteq S \wedge \delta S \subseteq \delta R \quad (8)$$

Obs.:

- clause $\delta S \subseteq \delta R$ ensures that implementations can only be **more defined**
- clause $R \cdot \delta S \subseteq S$ ensures that implementations can only be **more deterministic**
- Note that $\perp \vdash R$ still holds but, in general, $\top \vdash R$ requires R to be **entire**, since $\delta \top = id$.

Example

Let spec $S_{\nu, \epsilon}$ be

```
sqrt (x: real) r: real
pre  abs(x) <= nu
post abs(r*r-x) <= epsilon
```

Then, wherever $\nu_1 \leq \nu_2$ and $\epsilon_1 \geq \epsilon_2$,

$$S_{\nu_1, \epsilon_1} \vdash S_{\nu_2, \epsilon_2}$$

In the “limit”, $\dots \vdash S_{\infty, 0} = sq^\circ \vdash f$ where $f x = +\sqrt{x}$ or $f x = -\sqrt{x}$.

Refinement is a partial order

Reflexivity: $id \subseteq \vdash$, that is

$$S \vdash S$$

Transitivity: $\vdash \cdot \vdash \subseteq \vdash$, that is

$$S \vdash R \wedge R \vdash T \Rightarrow S \vdash T$$

Antisymmetry: $\vdash \cap \vdash^\circ \subseteq id$

$$S \vdash R \wedge R \vdash S \Rightarrow S = R$$

F-monotonicity:

$$S \vdash R \Rightarrow F S \vdash F R$$

Stepwise refinement

The laws of \vdash make it possible to refine a starting spec S along several steps,

$$S \vdash S_1 \vdash S_2 \vdash \dots$$

each one introducing more and more definition and/or determinism, and very often leading into a function (totally defined deterministic algorithm):

$$S \vdash S_1 \vdash S_2 \vdash \dots \vdash S_n \vdash f$$

What do we do after f ?

Back to $g \vdash f$

- Formally, $g \vdash f \equiv g = f$, that is, spec g is **extensionally** equivalent to implementation f .
- But there is more to it: in general, we think of f as being “more **efficient**” than g .
- Efficiency can only be formalized in the discipline of **algorithmic complexity** (out of scope here)
- We will study functional laws which add to efficiency and generalize well-known (`while`) loop generation and intercombination rules.

Main refinement strategies

- Refinement by “sequential loop” inter-combination: **fusion** and **absorption** laws:
 - “**Deforestation**” — removal of intermediate data-structures
- Refinement by “parallel loop” inter-combination: **mutual recursion** elimination:

On this purpose we will see Fokkinga’s law and its well-known corollary, the “banana-split” law.

Mutual recursion elimination

Consider the following pair of mutually dependent functions:

```
f(n) == if n = 0 then n else g(n - 1);
g(n) == if n = 0 then 1 else f(n - 1) + g(n - 1);
```

Can any of these functions — say g — be converted into a while loop?
In pointfree notation:

$$\begin{aligned} f \cdot [\underline{0}, suc] &= [id, g] \\ g \cdot [\underline{0}, suc] &= [\underline{1}, + \cdot \langle f, g \rangle] \end{aligned}$$

Mutual dependence made explicit

$$\begin{aligned} f \cdot [\underline{0}, suc] &= [id, \pi_2 \cdot \langle f, g \rangle] \\ g \cdot [\underline{0}, suc] &= [\underline{1}, + \cdot \langle f, g \rangle] \end{aligned} \quad \text{cf.} \quad \begin{array}{ccc} \mathbb{N}_0 & \xrightarrow{\cong} & \underbrace{1 + \mathbb{N}_0}_{F \mathbb{N}_0} \\ & \xleftarrow{\cong} & \end{array}$$

which is such that $F f = id + f$. So (+-absorption) $in = [id, suc]$ we can write

$$\begin{aligned} f \cdot in &= [id, \pi_2] \cdot F \langle f, g \rangle \\ g \cdot in &= [\underline{1}, +] \cdot F \langle f, g \rangle \end{aligned}$$

The mutual-recursion law

This situation is handled by the so-called **mutual-recursion law**, also called “Fokkinga law”:

$$\begin{cases} f \cdot in = h \cdot F \langle f, g \rangle \\ g \cdot in = k \cdot F \langle f, g \rangle \end{cases} \quad \equiv \quad \langle f, g \rangle = \langle \langle h, k \rangle \rangle$$

that is, in general

$$\begin{cases} f_1 \cdot in = h_1 \cdot F \langle f_1, \dots, f_n \rangle \\ \vdots \\ f_n \cdot in = h_n \cdot F \langle f_1, \dots, f_n \rangle \end{cases} \quad \equiv \quad \langle f_1, \dots, f_n \rangle = \langle \langle h_1, \dots, h_n \rangle \rangle$$

Proof

$$\begin{aligned} \langle f, g \rangle &= (\langle h, k \rangle) \\ \equiv & \quad \{ \text{cata-universal} \} \\ \langle f, g \rangle \cdot \text{in} &= \langle h, k \rangle \cdot F \langle f, g \rangle \\ \equiv & \quad \{ \times\text{-fusion twice (lhs and rhs)} \} \\ \langle f \cdot \text{in}, g \cdot \text{in} \rangle &= \langle h \cdot F \langle f, g \rangle, k \cdot F \langle f, g \rangle \rangle \\ \equiv & \quad \{ \text{"split" structural equality} \} \\ & \left\{ \begin{array}{l} f \cdot \text{in} = h \cdot F \langle f, g \rangle \\ g \cdot \text{in} = k \cdot F \langle f, g \rangle \end{array} \right. \end{aligned}$$

Example

Let $h = [id, \pi_2]$ and $k = [\underline{1}, +]$ in the example above:

$$\begin{aligned} \langle f, g \rangle &= \quad \{ \text{Fokkinga law} \} \\ &= (\langle [id, \pi_2], [\underline{1}, +] \rangle) \\ &= \quad \{ \text{exchange law} \} \\ &= (\langle [id, \underline{1}], \langle \pi_2, + \rangle \rangle) \end{aligned}$$

```
fg(n) == if n = 0 then mk_(0,1)
         else let p=fg(n-1)
              in mk_(p.#2,p.#1 + p.#2);
```

Example

Since $fg = \langle f, g \rangle$, we obtain $g = \pi_2 \cdot fg$. On the other hand, it is easy to extract g from

```
f(n) == if n = 0 then n else g(n - 1);  
g(n) == if n = 0 then 1 else f(n - 1) + g(n - 1);
```

as the standard Fibonacci function:

```
g(n) == if n = 0 then 1  
       else if n = 1 then 1  
       else g(n - 2) + g(n - 1);
```

Summary: we have calculated $\pi_2 \cdot fg$ as a **linear** version of Fibonacci ($g = \pi_2 \cdot fg$).

Corollary: “banana-split” (1)

Consider the function which computes the **average** of a non-empty list of natural numbers:

$$\text{average} \stackrel{\text{def}}{=} (/) \cdot \langle \text{sum}, \text{length} \rangle$$

Both sum and length are \mathbb{N}^+ catamorphisms:

$$\begin{aligned} \text{sum} &= ([id, +]) \\ \text{length} &= ([\underline{1}, \text{succ} \cdot \pi_2]) \end{aligned}$$

Function average performs two independent **traversals** of the argument list before division ($/$) takes place. Can we avoid this? “Banana-split” will fuse such two traversals.

Corollary: “banana-split” (2)

Let $h = i \cdot F \pi_1$ and $k = j \cdot F \pi_2$ in the mutual recursion law. Then

$$\begin{aligned} f \cdot in &= (i \cdot F \pi_1) \cdot F \langle f, g \rangle \\ &\equiv \quad \{ \text{composition is associative and } F \text{ is a functor} \} \\ f \cdot in &= i \cdot F (\pi_1 \cdot \langle f, g \rangle) \\ &\equiv \quad \{ \text{by } \times\text{-cancellation} \} \\ f \cdot in &= i \cdot F f \\ &\equiv \quad \{ \text{by cata-cancellation} \} \\ f &= (i) \end{aligned}$$

Corollary: “banana-split” (3)

Similarly, $g = \langle j \rangle$ will follow from $k = j \cdot F \pi_2$. Then, from the mutual recursion law we get

$$\langle \langle i \rangle, \langle j \rangle \rangle = \langle \langle i \cdot F \pi_1, j \cdot F \pi_2 \rangle \rangle$$

that is

$$\langle \langle i \rangle, \langle j \rangle \rangle = \langle (i \times j) \cdot \langle F \pi_1, F \pi_2 \rangle \rangle \quad (9)$$

This law provides us with a very useful tool for “parallel” loop inter-combination: “loops” $\langle i \rangle$ and $\langle j \rangle$ are fused together into a single “loop” $\langle (i \times j) \cdot \langle F \pi_1, F \pi_2 \rangle \rangle$.

Genericity of “banana-split”

Banana-split fuses two data-structure traversals (“loops”) in the generic sense. For instance,

$$average \stackrel{\text{def}}{=} \langle / \rangle \cdot \langle sum, length \rangle$$

still makes sense in the case of binary leaf trees, for

$$\begin{aligned} sum &= \langle [id, +] \rangle \\ length &= \langle [1, +] \rangle \end{aligned}$$

Again sum and $length$ can be fused together (bi-recursively).

Recursion elimination

Very common pattern in functional hylomorphisms:

$$\begin{aligned} f &: A \longrightarrow C \\ f &= p \rightarrow b, \theta \cdot \langle d, f \cdot e \rangle \end{aligned}$$

Diagram:

$$\begin{array}{ccccc} A & \xrightarrow{p?} & A + A & \xrightarrow{id + \langle d, e \rangle} & A + B \times A \\ f \downarrow & & & & \downarrow id + id \times f \\ C & \xleftarrow{[b, \theta]} & & & A + B \times C \end{array}$$

That is,

$$\langle \mu f \rangle :: [b, \theta] \cdot (id + id \times f) \cdot (id + \langle d, e \rangle) \cdot p?$$

More general intermediate type

By splitting $b = b_2 \cdot b_1$ we obtain a more general intermediate type

$$\begin{aligned} f & : A \rightarrow C \\ f & = p \rightarrow b_2 \cdot b_1, \theta \cdot \langle d, f \cdot e \rangle \end{aligned}$$

Diagram:

$$\begin{array}{ccccc} A & \xrightarrow{p?} & A + A & \xrightarrow{b_1 + \langle d, e \rangle} & D + B \times A \\ f \downarrow & & & & \downarrow id + id \times f \\ C & \xleftarrow{[b_2, \theta]} & & & D + B \times C \end{array}$$

Associative θ

The extra requirement (required by calculations to follow) that θ to be associative, ie for all i, j, k ,

$$\theta \cdot \langle \theta \cdot \langle i, j \rangle, k \rangle = \theta \cdot \langle i, \theta \cdot \langle j, k \rangle \rangle$$

leads us finally to the type scheme

$$\begin{array}{ccccc} A & \xrightarrow{p?} & A + A & \xrightarrow{b_1 + \langle d, e \rangle} & D + C \times A \\ f \downarrow & & & & \downarrow id + id \times f \\ C & \xleftarrow{[b_2, \theta]} & & & D + C \times C \end{array}$$

Can we eliminate recursion from this hylomorphism, eg. convert it to a while loop?

What is a while loop

A while loop

$$\underline{\text{while } p \text{ do } l} = (\neg \cdot p) \rightarrow id, (\underline{\text{while } p \text{ do } l}) \cdot l$$

is a very special case of hylomorphism $\llbracket R, S \rrbracket$ where S does all the work and R does nothing:

$$\begin{array}{ccccc} & & (id + l) \cdot (\neg \cdot p)? & & \\ & & \downarrow & & \downarrow id + (\underline{\text{while } p \text{ do } l}) \\ \underline{\text{while } p \text{ do } l} & \downarrow & A & \xrightarrow{\quad} & A + A \\ & & \downarrow & & \downarrow \\ & & A & \xleftarrow{\quad} & A + A \\ & & [id, id] & & \end{array}$$

Calculation plan

We want to convert the given hylo

$$f = p \rightarrow b, \theta \cdot \langle d, f \cdot e \rangle$$

into

$$\begin{aligned} f &= p \rightarrow b, w \cdot \langle d, e \rangle \\ w &= x \rightarrow y, w \cdot z \end{aligned}$$

the latter being the obvious `while`-loop

$$w = y \cdot (\text{while } (\neg \cdot x) \text{ do } z)$$

The unknowns of the problem are x, y and z .

Calculation

Clearly, finding w such that

$$w = \theta \cdot (id \times f)$$

is enough. We recall McCarthy-fusion laws

$$\begin{aligned} f \cdot (p \rightarrow g, h) &= p \rightarrow f \cdot g, f \cdot h \\ (p \rightarrow f, g) \cdot h &= (p \cdot h) \rightarrow (f \cdot h), (g \cdot h) \end{aligned}$$

and calculate:

$$\begin{aligned} &\langle \mu f :: \underbrace{p \rightarrow b, \theta \cdot \langle d, f \cdot e \rangle}_{Ff} \rangle \\ &= \{ \text{square rule, } \langle \mu f :: Ff \rangle = \langle \mu f :: F(Ff) \rangle \} \end{aligned}$$

Calculation (contd.)

$$\begin{aligned}
 & \langle \mu f :: p \rightarrow b, \theta \cdot \langle d, (p \rightarrow b, \theta \cdot \langle d, f \cdot e \rangle) \cdot e \rangle \rangle \\
 = & \quad \{ \text{McCarthy-fusion laws} \} \\
 & \langle \mu f :: p \rightarrow b, p \cdot e \rightarrow \theta \cdot \langle d, b \cdot e \rangle, \theta \cdot \langle d, \theta \cdot \langle d, f \cdot e \rangle \cdot e \rangle \rangle \\
 = & \quad \{ \times\text{-fusion and McCarthy-fusion again} \} \\
 & \langle \mu f :: p \rightarrow b, \\
 & \quad (p \cdot \pi_2 \rightarrow \theta \cdot (id \times b), \theta \cdot (id \times (\theta \cdot \langle d, f \cdot e \rangle))) \cdot \langle d, e \rangle \rangle \\
 = & \quad \{ \theta \text{ is associative} \} \\
 & \langle \mu f :: p \rightarrow b, \\
 & \quad p \cdot \pi_2 \rightarrow \theta \cdot (id \times b), \theta \cdot \langle \theta \cdot (id \times d), f \cdot e \cdot \pi_2 \rangle \cdot \langle d, e \rangle \rangle
 \end{aligned}$$

Calculation (contd.)

We now focus on the inner conditional:

$$\begin{aligned}
 & p \cdot \pi_2 \rightarrow \theta \cdot (id \times b), \theta \cdot \langle \theta \cdot (id \times d), f \cdot e \cdot \pi_2 \rangle \\
 = & \quad \{ \times\text{-absorption} \} \\
 & p \cdot \pi_2 \rightarrow \theta \cdot (id \times b), \theta \cdot (id \times f) \cdot \langle \theta \cdot (id \times d), e \cdot \pi_2 \rangle \\
 = & \quad \{ \text{pattern matching (recall assumption } w = \theta \cdot (id \times f)) \} \\
 & \underbrace{\underbrace{p \cdot \pi_2}_x \rightarrow \underbrace{\theta \cdot (id \times b)}_y, \underbrace{\theta \cdot (id \times f)}_w \cdot \underbrace{\langle \theta \cdot (id \times d), e \cdot \pi_2 \rangle}_z}_{w}
 \end{aligned}$$

So we've found tail-recursive solution

$$w = p \cdot \pi_2 \rightarrow \theta \cdot (id \times b), w \cdot \langle \theta \cdot (id \times d), e \cdot \pi_2 \rangle$$

Calculation (contd.)

Altogether:

$$\begin{aligned}
 f & = p \rightarrow b, w \cdot \langle d, e \rangle \\
 w & = p \cdot \pi_2 \rightarrow \theta \cdot (id \times b), w \cdot \langle \theta \cdot (id \times d), e \cdot \pi_2 \rangle
 \end{aligned}$$

Quite often $b = \underline{u}$, where u is the unit of θ ($a \theta u = a$). We then get a simpler w :

$$\begin{aligned}
 w & = p \cdot \pi_2 \rightarrow \pi_1, w \cdot \langle \theta \cdot (id \times d), e \cdot \pi_2 \rangle \\
 & = \pi_1 \cdot (\underline{while} \neg \cdot p \cdot \pi_2 \underline{do} \langle \theta \cdot (id \times d), e \cdot \pi_2 \rangle)
 \end{aligned}$$

Example - factorial

From

$$fac = (=0) \rightarrow \underline{1}, mul \cdot \langle id, fac \cdot pred \rangle$$

we get VDM-SL functions

```
fac(n) == if n=0 then 1 else w(n,n-1)
w(m,i) == if i=0 then m else w(m * i, i-1 )
```

The next slide shows how the while loop can be made explicit by moving from functions to operations.

Example - factorial

```
fac : nat ==> nat
fac(n) ==
  if n=0 then return 1
  else (dcl m: nat := n,
        i: nat := n -1;
        while (i <> 0) do
          (m := m * i; i := i-1);
        return m;
  );
```

Other results

For $b = \underline{u}$ there is another recursion removal law which we could prove similarly:

$$\begin{aligned} f & : A \longrightarrow C \\ f & = p \rightarrow \underline{u}, \theta \cdot \langle d, f \cdot e \rangle \end{aligned}$$

is equivalent to

$$\begin{aligned} f & = w \cdot \langle \underline{u}, id \rangle \\ w & = p \cdot \pi_2 \rightarrow \pi_1, w \cdot \langle \theta \cdot (id \times d), e \cdot \pi_2 \rangle \end{aligned}$$

The corresponding VDM-SL version of factorial is presented in the slide which follows:

Example - “another” factorial

```
fac : nat ==> nat
fac(n) ==
  (dcl m: nat := 1,
   i: nat := n;
   while (i <> 0) do
     (m := m * i; i := i - 1);
   return m
  );
```

For versus while loops

VDM-SL/VDM++ syntax includes for loops. Therefore, the two while loops above can be converted into, respectively,

```
fac(n) ==
  if n=0 then return 1
  else (dcl m: nat := n;
        for i=n-1 to 1 by -1 do m := m * i;
        return m;
  );
and
fac(n) ==
  (dcl m: nat := 1;
   for i = n to 1 by -1 do m := m * i;
   return m
  );
```

Data refinement in full

Simultaneous **algorithm/data** refinement: given

- a spec $A \xleftarrow{S} B$
- abstraction function $A \xleftarrow{F_1} C$
- representation relation $D \xleftarrow{R_2} B$

then $C \xleftarrow{I} D$ will be said to **implement** S iff

$$S \vdash F_1 \cdot I \cdot R_2 \quad \begin{array}{ccc} & A & \xleftarrow{S} B \\ F_1 \uparrow & & \downarrow R_2 \\ & C & \xleftarrow{I} D \end{array} \quad (10)$$

Analysis of refinement equation


- The above refinement equation is to be solved for I (the unknown), and will in general exhibit more than one solution.
- $S \vdash F_1 \cdot I \cdot R_2$ means

$$F_1 \cdot I \cdot R_2 \cdot \delta S \subseteq S \quad \wedge \quad \delta S \subseteq \delta (F_1 \cdot I \cdot R_2)$$

- In case $F_i = R_i = id$ ($i = 1, 2$) — no data refinement involved — it boils down to algorithmic refinement:

$$S \vdash id \cdot I \cdot id$$

Example



recall

$$R \rightarrow S, T \stackrel{\text{def}}{=} (S \cdot \delta R) \cup T \cdot (id - \delta R)$$

Note how non-determinism of implementation is coped with by the target abstraction function.

Solving refinement equations

Since $\delta(S \cdot R) = \delta(\delta S \cdot R)$, the second clause above rewrites to

$$\delta S \subseteq \delta(\delta F_1 \cdot (I \cdot R_2))$$

In case $F_1(f_1)$ is entire:

$$\delta S \subseteq \delta(I \cdot R_2)$$

In case spec S and $F_1(f_1)$ are entire and $R_2 = f_2^\circ$, I will be entire and such that

$$I \subseteq f_1^\circ \cdot S \cdot f_2$$

Functional solutions

Case in which all entities in a refinement equation are total functions (note the lowercase letters):

$$f_1 \cdot i = s \cdot f_2 \quad (11)$$

- Example: $i = f^*$ will implement $s = \mathcal{P}f$ under data-refinement $f_1 = f_2 = elems$.
- $i = f^*$ is not a unique solution. These arise wherever f_1 is iso (f_1° is a function):

$$i = f_1^\circ \cdot s \cdot f_2$$

This appeals to calculating i by cata-fusion over inductive implementation type D .

Example

Set by list refinement:

$$(a \text{ belongs}) = (a \in) \cdot elems$$

($f_1 = id$):

$$\begin{array}{ccc}
 & (a \in) & \\
 2 & \longleftarrow \mathcal{P}A & \\
 id \uparrow & & \uparrow elems \\
 2 & \longleftarrow A^* & \\
 & a \text{ belongs} &
 \end{array}$$

We know that $elems = \langle ins \rangle$. Since target function is a list cata $(a \text{ belongs}) = \langle \beta \rangle$, by cata-fusion refinement equation will hold provided $(a \in) \cdot ins = \beta \cdot (id + id \times (a \in))$ holds.

Example (cont.)

Let $\beta = [\beta_1, \beta_2]$.

- Since $a \in \emptyset = \text{FALSE}$, we calculate $\beta_1 = \underline{\text{FALSE}}$.
- We are left with

$$a \in (\{x\} \cup s) = \beta_2(x, a \in s)$$

From $a \in \{x\} \cup s = (a \in \{x\}) \vee (a \in s)$, we infer $\beta_2(x, b) \equiv a = x \vee b$.

- All in all:

```
belongs(a)(l) ==  
  if l = [] then false  
  else (a = hd l) or belongs(a)(tl l)
```

Bibliografia